

CONFERENCE

# **IOP** Conference Series

## Earth and Environmental Science

**1st Workshop on Metrology for Agriculture  
and Forestry (METROAGRIFOR)**

# 275

VOLUME 275 – 2019

1–2 October 2018  
Aversa, Italy

**EDITOR**  
Enrico Ferra (Ferrara)

The open access journal for conference proceedings

[openaccess.iop.org/jpc](http://openaccess.iop.org/jpc)

**IOP** Publishing

PAPER • OPEN ACCESS

## Classification of large green chilli maturity using deep learning

To cite this article: Y Hendrawan *et al* 2021 *IOP Conf. Ser.: Earth Environ. Sci.* **924** 012009

View the [article online](#) for updates and enhancements.

You may also like

- [Model of optimal organization maturity management under conditions of interference and uncertainty](#)  
Mikhail Dorrer
- [Microsensors and image processing for single oocyte qualification: toward multiparametric determination of the best time for fertilization](#)  
B Wacogne, I Ivascu, R Zeggari et al.
- [Biospeckle image processing algorithms for non-destructive differentiation between maturity and ripe stages of Indian climacteric fruits and evaluation of their ripening period](#)  
S Kumari and A K Nirala



**244<sup>th</sup> Electrochemical Society Meeting**

October 8 – 12, 2023 • Gothenburg, Sweden

50 symposia in electrochemistry & solid state science

Abstract submission deadline:  
**April 7, 2023**

Read the call for papers &  
**submit your abstract!**

# Classification of large green chilli maturity using deep learning

**Y Hendrawan<sup>\*1</sup>, B Rohmatulloh<sup>1</sup>, I Prakoso<sup>2</sup>, V Liana<sup>3</sup>, M R Fauzy<sup>4</sup>, R Damayanti<sup>1</sup>, M B Hermanto<sup>1</sup>, D F Al Riza<sup>1</sup>, Sandra<sup>1</sup>**

<sup>1</sup>Laboratory of Mechatronics and Agro-industrial Machineries, Department of Agricultural Engineering, Universitas Brawijaya, Jl. Veteran, Malang, ZIP 65145, Indonesia

<sup>2</sup>Department of Agricultural Product Technology, Universitas Brawijaya, Jl. Veteran, Malang, ZIP 65145, Indonesia

<sup>3</sup>Department of Agroindustrial Technology, Universitas Brawijaya, Jl. Veteran, Malang, ZIP 65145, Indonesia

<sup>4</sup>Department of Industrial Engineering, Universitas Merdeka, Jl. Terusan Raya Dieng 62-64, Malang, ZIP 65146, Indonesia

E-mail: yusuf\_h@ub.ac.id

**Abstract.** Chili (*Capsicum annuum* L.) is the source of various nutraceutical small molecules, such as ascorbic acid (vitamin C), carotenoids, tocopherols, flavonoids, and capsinoids. The purpose of this study was to classify the maturity stage of large green chili into three maturity levels, i.e. maturity 1 (maturity index 1 / 34 days after anthesis (DAA)), maturity 2 (maturity index 3 / 47 DAA), and maturity 3 (maturity index 5 / 60 DAA) by using convolutional neural networks (CNN) based deep learning and computer vision. Four types of pre-trained networks CNN were used in this study i.e. SqueezeNet, GoogLeNet, ResNet50, and AlexNet. From the overall sensitivity analysis results, the highest maturity classification accuracy of large green chili was 93.89% which can be achieved when using GoogLeNet with SGDmoptimizer and learning rate of 0.00005. However, in further testing using testing-set data, the highest classification accuracy based on confusion matrix was reaching 91.27% when using the CNN SqueezeNet model with RMSProp optimizer and a learning rate of 0.0001. The combination of the CNN model and the low-cost digital commercial camera can later be used to detect the maturity of large green chili with the advantages of being non-destructive, rapid, accurate, low-cost, and real-time.

## 1. Introduction

Chili (*Capsicum annuum* L.) is the source of various nutraceutical small molecules, such as ascorbic acid (vitamin C), carotenoids, tocopherols, flavonoids, and capsinoids [1]. Chili is rich in bioactive contents such as carotenoids ( $\beta$ -carotene and  $\beta$ -cryptoxanthin), capsaicinoids, flavonoids, and micronutrients, such as phenolic compounds and vitamin C with antioxidant properties. The content of these compounds is influenced by several factors i.e. hybrid varieties, maturity levels at harvest, climatic conditions, and treatment of storage and processing of chili [2]. Large green chili has a higher vitamin C content than other types of chili. One factor that can affect the content of vitamin C in chili is the level of maturity. The level of maturity of chili can be seen from color changes, and color will affect quality.



The higher the maturity index of the chili, the more intense the color of the chili so that the nutritional content and quality of the chili will be higher. Chili at a higher maturity level has a higher vitamin C content compared to chili at a low level of maturity. Increased accumulation of ascorbic acid or vitamin C in chili is associated with an increase in chili shelf life and improved post-harvest chili quality [3].

In general, chili has nine maturity indices [4], where differences in each index can be seen based on increasingly mature color changes as shown in Figure 1. Each maturity index has characteristics as follows: Index 1 light yellowish green; Index 2 bright and shiny green; Index 3 bright green, shiny, and slippery; Index 4 dark green, glistening, and slippery; Index 5 dark green or blackish and shiny green; Index 6 green mixed with red, shiny, and waxy; Index 7 dominant colored red mixed with green, slightly shiny, very slippery; Index 8 the dominant colored is red and there is a slight green or overall bright red color, shiny, and slippery; Index 9 overall dark red or blackish red, slightly shiny, and slippery.



**Figure 1.** Chili maturity index.


Hendrawan et al. [5-8] have proven the effectiveness of computer vision in the classification and identification of agricultural products with various advantages including precision, rapid, non-destructive, real-time, and low-cost. Convolutional neural networks (CNN) can improve the performance of computer vision in classifying and identifying agricultural products. Parvathi and Selvi [9] have proven CNN's excellence in using the ResNet50 pre-trained network for detecting coconut maturity from real-time images on farms with an accuracy rate of up to 99%. Behera et al. [10] have successfully identified and classified papaya fruits using CNN with several pre-trained networks such as ResNet101, ResNet50, ResNet18, VGG19, VGG16, GoogLeNet, and AlexNet. The accuracy results are also very good because the CNN models have managed to achieve 100% accuracy. Ismail and Malik [11] have developed research to grading apples and bananas at several maturity levels using several CNN pre-trained network models i.e. ResNet, DenseNet, MobileNetV2, NASNet, and EfficientNet. The results show a high accuracy value of 96.7% for apples and 93.8% for bananas. This shows the efficacy of the CNN model that has been developed. Nasiri et al. [12] in their research sorted dates into several classifications of maturity using the CNN model with VGG-16 architecture. The result shows good accuracy of 96.98%. Wan and Goudos [13] have succeeded in classifying several fruits such as apples, oranges, and mangoes into several ripeness categories using the CNN model. The highest accuracy for apples was 92.51%, while oranges were 90.73%, and mangoes were 88.94%. In another study, Ni et al. [14] also proved the effectiveness of CNN in identifying the ripeness of berries with high accuracy of 97.3%. The reliability of CNN in identifying fruit maturity was also demonstrated in the study of Habaragamuwa et al. [15] who have succeeded in classifying strawberries (mature and immature) using a deep convolutional neural network (DCNN). The accuracy achieved in this study reached 88.03%.

However, from various studies on computer vision and CNN in modeling the maturity of agricultural products, there are no studies that have examined the benefits of computer vision and CNN in classifying and identifying large green chili maturity. This study aims to classify the maturity stage of large green chili into three maturity levels, i.e. maturity 1 (maturity index 1 / 34 days after anthesis (DAA)), maturity 2 (maturity index 3 / 47 DAA), and maturity 3 (maturity index 5 / 60 DAA) by using CNN and computer vision. The level of maturity of this chili is based on the research of Hendrawan et al. [16] as a basis for classification.


## 2. Materials and methods

In this study, large green chilies were harvested from chili plantations in Tawang Argo Village, KarangPloso District, Malang, Indonesia. Maturity 1 was harvested at 34 DAA, maturity 2 was harvested at 47 DAA, while maturity 3 was harvested at 60 DAA. This study used a low-cost digital commercial camera to collect large green chili image data. The image acquisition process was carried out using a closed black box with evenly distributed lighting over the surface of the large green chili object. The light was provided by two 22W lamps (EFD25N/22, National Corporation, Japan). Light intensity over the object surface was uniform at 300 lux in the center of the region during image acquisition. A low-cost digital commercial camera (Logitech C270 HD camera 3-megapixel snapshots) was used for image acquisition with a distance of 300 mm from the camera to the object's surface. From the image acquisition process, the image was obtained with a resolution of  $300 \times 300$  pixels in JPEG format. The augmentation process of image data is carried out to increase the amount of data. Each level of maturity used a sample of 100 chilies. After the augmentation stage, 400 chili image data were obtained for the training and validation process. Then at each level of maturity, 20 more chili samples were taken, which after augmentation became 80 image data for the testing process. A total of 1200 image data with three maturity categories i.e. maturity 1, maturity 2, and maturity 3 were used as training and validation data. Image data was divided into two parts i.e. 70% for training data and 30% for validation data.

Figure 2 shows an example of large green chili with maturity 1, maturity 2, and maturity 3. Large green chili in each maturity class looks almost the same and is difficult to distinguish by observations from external appearances. The deep learning method was used to model image data in categorizing the quality of large green chili. Four types of CNN pre-trained networks were used in this study i.e. SqueezeNet, GoogLeNet, ResNet50, and AlexNet. The CNN SqueezeNet algorithm was described in the research of Ucar and Korkmaz [17], GoogLeNet in the study of Raikar et al. [18], ResNet50 in the study of Mkonyi et al. [19], and AlexNet on Jiang et al. [20].



**Figure 2.** 300×300 pixels image of large green chili in different maturity levels: a) maturity 1; b) maturity 2; c) maturity 3.



**Figure 3.** Structure of CNN model to classify large green chili maturity.

The CNN structure for classifying large green chili maturity, in general, can be seen in Figure 3. Some of the parameters that were set on each CNN pre-trained included: optimizer (SGDm, Adam,

RMSProp) [21], initial learning rate (0.00005 and 0.0001) [22], epoch 20, minibatch size 20 [23], sequence padding value = 0, sequence padding direction = right, L2Regularization = 0.00001, learning rate drop factor = 0.1, learning rate drop period = 10, and momentum = 0.9. After the CNN modeling process had been carried out, the best model was tested on 80 data sets in each quality category. The testing data set was image data of large green chili taken separately from training and validation data. The performance of the CNN model was measured from the classification accuracy of the testing-set data using the confusion matrix method [24].

### 3. Results and discussion


The performance of CNN's pre-trained network can be seen in Table 1. Four models of the pre-trained network were used to classify the maturity of large green chili i.e. AlexNet, GoogLeNet, ResNet50, and SqueezeNet. Sensitivity analysis was carried out by varying the optimizer method i.e. SGDm, Adam, and RMSProp, and varying the initial learning rates of 0.00005 and 0.0001. Based on the obtained results, it showed that the four pre-trained networks CNN models produced different classification accuracy with an accuracy ranging from the lowest 82.22% to the highest 93.89%.

**Table 1.** Performance of pre-trained network CNN to classify large green chili maturity.


Architecture	Optimizer	Learning rate	Accuracy (%)	Time (minutes)
AlexNet	SGDm	0.00005	92.22	78
	Adam	0.00005	86.11	78
	RMSProp	0.00005	86.39	78
	SGDm	0.0001	86.94	75
	Adam	0.0001	83.61	78
	RMSProp	0.0001	82.22	84
GoogLeNet	SGDm	0.00005	93.89	181
	Adam	0.00005	91.94	149
	RMSProp	0.00005	88.89	148
	SGDm	0.0001	87.78	148
	Adam	0.0001	93.89	149
	RMSProp	0.0001	89.72	149
ResNet50	SGDm	0.00005	90.83	350
	Adam	0.00005	90.56	341
	RMSProp	0.00005	89.72	369
	SGDm	0.0001	91.39	357
	Adam	0.0001	93.06	358
	RMSProp	0.0001	88.61	374
SqueezeNet	SGDm	0.00005	87.78	83
	Adam	0.00005	91.11	79
	RMSProp	0.00005	88.61	80
	SGDm	0.0001	86.94	80
	Adam	0.0001	87.22	78
	RMSProp	0.0001	92.78	79

Overall, based on the value of the initial learning rate, it was proven that the learning rate of 0.00005 produced a higher average classification accuracy of 89.84% compared to the learning rate of 0.0001 which resulted in an average classification accuracy of 88.68%. Based on CNN's pre-trained network architecture, the GoogLeNet model had the highest average classification of 91.01% followed by ResNet50, Squeezenet, and AlexNet with average classification accuracy values of 90.69%, 89.07%, and 86.25%, respectively. These results are in line with research conducted by Li et al. [25] which proved the performance effectiveness of GoogLeNet for classification. However, Table 1 also shows

the weakness of ResNet50 and GoogLeNet is that the training process required was very long with an average learning time of 358 minutes for ResNet50 and 154 minutes for GoogLeNet. The fastest learning process was achieved when using the CNN AlexNet model, which was about 78.5 minutes. Based on the optimizer method used, it was proven that SGDm produced the highest average classification accuracy of 89.72% compared to Adam and RMSProp which had an average classification accuracy of 89.68% and 88.36%, respectively. From the overall results of sensitivity analysis, the highest classification accuracy was 93.89% which can be achieved when using GoogLeNet with SGDm optimizer and learning rate 0.00005.



**Figure 4.** Performance of CNN to classify large green chili maturity using pre-trained network: (a) GoogLeNet (optimizer = SGDm, learning rate = 0.00005); (b) GoogLeNet (optimizer = Adam, learning rate = 0.0001); (c) ResNet50 (optimizer = Adam, learning rate = 0.0001); (d) SqueezeNet (optimizer = RMSProp, learning rate = 0.0001); (e) AlexNet (optimizer = SGDm, learning rate = 0.00005).



**Figure 5.** Performance of testing-set data using a confusion matrix: (a) GoogLeNet (optimizer = SGDm, learning rate = 0.00005); (b) GoogLeNet (optimizer = Adam, learning rate = 0.0001); (c) ResNet50 (optimizer = Adam, learning rate = 0.0001); (d) SqueezeNet (optimizer = RMSProp, learning rate = 0.0001); (e) AlexNet (optimizer = SGDm, learning rate = 0.00005).

The training process in the five best CNN models can be seen in Figure 4. From Figure 4, all CNN models showed an effective training process performance where the accuracy value increased with increasing iteration[26]. The opposite applied to the loss value, where the loss value decreased with

increasing iteration. Almost the same patterns were shown by the five best CNN models. The training and validation performance chart patterns appeared to move quickly at the initial epoch and converged at the next epoch where the accuracy value moved increasingly converging to a value close to 100% and the loss value converged closer to the value 0. The validation value, both accuracy, and loss moved according to the training value. In terms of the stability of the learning process, it can be seen in Figure 4 that GoogLeNet with Adam optimizer and learning rate of 0.0001 showed a fairly stable training and validation process compared to other CNN models.

After the best results were obtained in the training and validation process, the next step was testing the performance of the CNN model using the testing-set data. Of the five best CNN models when tested using the testing-set data, they all produced the same performance, the same accuracy value, and the same error value [26]. So that for the confusion matrix in this study, one confusion matrix result was shown representative of the best five CNN models. The results of the confusion matrix can be seen in Figure 5. From the results of the confusion matrix, it appeared that the highest average accuracy of the testing-set data was 91.27% achieved by SqueezeNet with RMSProp optimizer and learning rate 0.0001, where this accuracy value was very high for classifying the maturity of large green chili. In the large green chili class of maturity 3, the CNN model was able to accurately calculate 100% without the slightest error. While in the maturity 1 and maturity 2 class, the CNN model made an error of 12.2% and 25.74%, respectively, and was still able to classify the maturity 1 and maturity 2 class with an accuracy of 87.80% and 74.26%, respectively. With this accuracy result, it can be concluded that the CNN model that had been built can work effectively to classify large green chili into maturity 1, maturity 2, and maturity 3 classes. In future work, the combination of the CNN model and the low-cost digital commercial camera can be used to detect the maturity of large green chili with the advantages of being non-destructive, rapid, accurate, low-cost, and real-time.

#### 4. Conclusions

The maturity of large green chili was divided into three classes i.e. maturity 1 (maturity index 1 / 34 days after anthesis (DAA)), maturity 2 (maturity index 3 / 47 DAA), and maturity 3 (maturity index 5 / 60 DAA). CNN's pre-trained network models used in this study included AlexNet, GoogLeNet, ResNet50, and SqueezeNet. The research results showed very high accuracy in the training and validation process. Five best CNN models i.e. GoogLeNet (optimizer = SGDM, learning rate = 0.00005); GoogLeNet (optimizer = Adam, learning rate = 0.0001); ResNet50 (optimizer = Adam, learning rate = 0.0001); SqueezeNet (optimizer = RMSProp, learning rate = 0.0001); AlexNet (optimizer = SGDM, learning rate = 0.00005) were able to achieve training and validation accuracy up to 93.89%. In further testing using the testing-set data, the highest classification accuracy based on the confusion matrix was reaching 91.27%. The combination of the CNN model and the low-cost digital commercial camera can later be used to detect the maturity of large green chili with the advantages of being non-destructive, rapid, accurate, low-cost, and real-time.

#### 5. References

- [1] Conforti F, Statti G A, Menichini, F 2007 Chemical and biological variability of hot pepper fruits (*Capsicum annum var. acuminatum L.*) in relation to maturity stage. *Food Chem.* **102** 4 1096-1104
- [2] Iqbal Q, Amjad M, Asi M R, Arino A 2013 Characterization of capsaicinoids and antioxidants in hot peppers as influenced by hybrid and harvesting stage. *Plant Foods and Hum. Nutr.* **68** 358-363.
- [3] Bae H, Jayaprakasha G K, Kevin C, Kil S Y, Daniel I L, John J, Bhimanagouda S P 2014 Ascorbic acid, capsaicinoid, and flavonoid aglycone concentrations as a function of fruit maturity stage in greenhouse-grown peppers. *J. Food Compos. Anal.* **33** 195-202
- [4] Cantwell M 2009 Maturation and maturity indices *Postharvest technology Short Course* chapter 6 Postharvest Technology Book. University of California. Davis

- [5] Hendrawan Y, Widyaningtyas S, Sucipto 2019 Computer vision for purity, phenol, and pH detection of luwak coffee green bean. *TELKOMNIKA*. **17** 6 3073-3085
- [6] Hendrawan Y, Fauzi M R, Khoirunnisa N S, Andreane M, Hartianti P O, Halim T D, Umam C 2018 Development of colour co-occurrence matrix (CCM) texture analysis for biosensing. *IOP Conf. Ser.: Earth and Environ. Sci.* **230** 012022
- [7] Hendrawan Y, Amini A, Maharani D M, Sutan S M 2019 Intelligent non-invasive sensing method in identifying coconut (*Coco nucifera var. Ebunea*) ripeness using computer vision and artificial neural network. *PERTANIKA J. Sci. Technol.* **27** 31317-1339
- [8] Hendrawan Y, Sakti I M, Wibisono Y, Rachmawati M, Sutan S M 2018 Image analysis using color co-occurrence matrix textural features for predicting nitrogen content in spinach. *TELKOMNIKA*. **16** 6 2712-2724
- [9] Pavarthi S and Selvi S T 2021 Detection of maturity stages of coconuts in complex background using Faster R-CNN model. *Biosyst. Eng.* **202** 119-132
- [10] Behera S K, Rath A K, Sethy P K 2020 Maturity status classification of papaya fruits based on machine learning and transfer learning approach. *Inf. Process. Agric.* **8** 2 244-250
- [11] Ismail N and Malik O A 2021 Real-time visual inspection system for grading fruits using computer vision and deep learning techniques. *Inf. Process Agric.* In Press
- [12] Nasiri A, Garavand A T, Zhang Y D 2019 Image-based deep learning automated sorting of date fruit. *Postharvest Biol. Technol.* **153** 133-141
- [13] Wan S and Goudos S 2020 Faster R-CNN for multi-class fruit detection using a robotic vision system. *Computer Networks*. **168** 107036
- [14] Ni X, Li C, Jiang H, Takeda F 2021 Three-dimensional photogrammetry with deep learning instance segmentation to extract berry fruit harvestability traits *ISPRS J. Photogramm. Remote Sens.* **171** 297-309
- [15] Habaragamuwa H, Ogawa Y, Suzuki T, Shiigi T, Ono M, Kondo N 2018 Detecting greenhouse strawberries (mature and immature), using deep convolutional neural network *Engineering in Agriculture, Environment and Food*. **11** 3 127-138
- [16] Hendrawan Y, Utami R, Nurseta D Y, Daisy, Nuryani S, Maharani D M, Sandra 2021 Classification of total carotene and quality of chili pepper (*Capsicum frutescens*) based on image analysis *IOP Conf. Ser.: Earth and Environ. Sci.* **733** 012005
- [17] Ucar F and Korkmaz D 2020 COVIDiagnosis-Net: deep bayes-squeezenet based diagnosis of the coronavirus disease 2019 (covid-19) from x-ray images *Medical Hypotheses*. **140** 109761
- [18] Raikar M M, Meena S M, Kuchanur C, Girraddi S, Benagi P 2020 Classification and grading of okra-ladies finger using deep learning *Procedia Comput. Sci.* **171** 2380-2389
- [19] Mkonyi L, Rubanga D, Richard M, Zekeya N, Sawahiko S, Maiseli B, Machuve D 2020 Early identification of Tutaabsoluta in tomato plants using deep learning *Sci. Afr.* **10** e00590.
- [20] Jiang B, He J, Yang S, Fu H, Li T, Song H, He D 2019 Fusion of machine vision technology and AlexNet-CNNs deep learning network for the detection of postharvest apple pesticide residues *Artif Intel Agric.* **1** 1-8
- [21] Manninen H, Ramlal C J, Singh A, Rocke S, Kilter J, Landsberg M 2021 Toward automatic condition assessment of high-voltage transmission infrastructure using deep learning techniques *Int. J. Electr Power Energy Syst.* **128** 106726
- [22] Thenmozhi, K, and Redy, U S 2019 Crop pest classification based on deep convolutional neural network and transfer learning. *Comput Electron. Agric.* **164** 104906
- [23] Tian C, Xu Y, Zuo W 2020 Image denoising using deep CNN with batch renormalization. *Neural Netw.* **121** 461-473
- [24] Ruuska S, Hamalainen W, Kajava S, Mughal M, Matilainen P, Mononen J 2018 Evaluation of the confusion matrix method in the validation of an automated system for measuring feeding behaviour of cattle *Neural Netw.* **148** 56-62
- [25] Li Y, Wang H, Dang L M, Niaraki A S S, Moon H 2020 Crop pest recognition in natural scenes using convolutional neural networks *Computers and Electronics in Agriculture*. **169** 105174

- [26] Hendrawan Y, Damayanti R, Al-Riza D F, Hermanto M B 2021 Classification of water stress in cultured Sunagoke moss using deep learning *TELKOMNIKA*. **19** 5 1594-1604

# Classification of large green chilli maturity using deep learning

---

## ORIGINALITY REPORT

---

16%

SIMILARITY INDEX

%

INTERNET SOURCES

16%

PUBLICATIONS

%

STUDENT PAPERS

---

## PRIMARY SOURCES

---

- 1** Nazrul Ismail, Owais A. Malik. "Real-time Visual Inspection System for Grading Fruits using Computer Vision and Deep Learning Techniques", Information Processing in Agriculture, 2021 1%  
Publication

---
- 2** Khalid El Asnaoui, Youness Chawki. "Using X-ray images and deep learning for automated detection of coronavirus disease", Journal of Biomolecular Structure and Dynamics, 2020 1%  
Publication

---
- 3** Iness Bettaieb Rebey, Sarra Kefi, Soumaya Bourgou, Ines Ouerghemmi, Riadh Ksouri, Moufida Saidani Tounsi, Brahim Marzouk. "Ripening Stage and Extraction Method Effects on Physical Properties, Polyphenol Composition and Antioxidant Activities of Cumin (Cuminum cyminum L.) Seeds", Plant Foods for Human Nutrition, 2014 1%  
Publication

---

4

Subramanian Parvathi, Sankar Tamil Selvi. "Detection of maturity stages of coconuts in complex background using Faster R-CNN model", Biosystems Engineering, 2021

Publication

---

1 %

5

Tyler G. Dowd, Mao Li, G. Cody Bagnall, Andrea Johnston, Christopher N. Topp. "Root system architecture and environmental flux analysis in mature crops using 3D root mesocosms", Frontiers in Plant Science, 2022

Publication

---

1 %

6

Solemane Couliably, Bernard Kamsu-Foguem, Dantouma Kamissoko, Daouda Traore. "Deep learning for precision agriculture: a bibliometric analysis", Intelligent Systems with Applications, 2022

Publication

---

1 %

7

V.G. Dhanya, A. Subeesh, N.L. Kushwaha, D.K. Vishwakarma, T. Nagesh Kumar, G. Ritika, A.N. Singh. "Deep learning based computer vision approaches for smart agricultural applications", Artificial Intelligence in Agriculture, 2022

Publication

---

1 %

8

Ana M Ribes - Moya, Ana M Adalid, Maria D Raigón, Pilar Hellín, Ana Fita, Adrián Rodríguez - Burruezo. " Variation in flavonoids in a collection of peppers ( sp.)

1 %

under organic and conventional cultivation: effect of the genotype, ripening stage, and growing system ", Journal of the Science of Food and Agriculture, 2020

Publication

---

9

Tej Bahadur Chandra, Kesari Verma, Bikesh Kumar Singh, Deepak Jain, Satyabhuwan Singh Netam. "Coronavirus Disease (COVID-19) Detection in Chest X-Ray Images using Majority Voting Based Classifier Ensemble", Expert Systems with Applications, 2020

Publication

---

1 %

10

Amin Nasiri, Mahmoud Omid, Amin Taheri-Garavand. "An automatic sorting system for unwashed eggs using deep learning", Journal of Food Engineering, 2020

Publication

---

1 %

11

Mike O. Ojo, Azlan Zahid. "Deep Learning in Controlled Environment Agriculture: A Review of Recent Advancements, Challenges and Prospects", Sensors, 2022

Publication

---

1 %

12

Enes Ayan, Hasan Erbay, Fatih Varçın. "Crop pest classification with a genetic algorithm-based weighted ensemble of deep convolutional neural networks", Computers and Electronics in Agriculture, 2020

Publication

---

1 %

13

Francisco López de la Rosa, José L. Gómez-Sirvent, Roberto Sánchez-Reolid, Rafael Morales, Antonio Fernández-Caballero. "Geometric transformation-based data augmentation on defect classification of segmented images of semiconductor materials using a ResNet50 convolutional neural network", Expert Systems with Applications, 2022

Publication

---

1 %

14

Weiwei Wang, Cheng Li, Kui Wang, Lingling Tang, Pedro Final Ndiluau, Yuhe Cao. "Sugarcane stem node detection and localization for cutting using deep learning", Frontiers in Plant Science, 2022

Publication

---

1 %

15

József Deli, Péter Molnár, Zoltán Matus, Gyula Tóth. " Carotenoid Composition in the Fruits of Red Paprika ( var. ) during Ripening; Biosynthesis of Carotenoids in Red Paprika ", Journal of Agricultural and Food Chemistry, 2001

Publication

---

1 %

16

Ashkan Banan, Amin Nasiri, Amin Taheri-Garavand. "Deep learning-based appearance features extraction for automated carp species identification", Aquacultural Engineering, 2020

&lt;1 %

17

Hendrawan, Y.. "Neural-Intelligent Water Drops algorithm to select relevant textural features for developing precision irrigation system using machine vision", *Computers and Electronics in Agriculture*, 201107

Publication

---

18

Xiu Shu, Di Yuan, Qiao Liu, Jiaqi Liu. "Adaptive weight part-based convolutional network for person re-identification", *Multimedia Tools and Applications*, 2020

Publication

---

19

Vrushali Kulkarni, Pranali Kosamkar, Chanavi Singh, Purva Ingle, Vedant Modi. "Chapter 37 Detection and Classification of Diseases and Maturity of Dragon Fruits", *Springer Science and Business Media LLC*, 2022

Publication

---

20

Roberlanio De Oliveira Melo, Marly G. F. Costa, Cicero F. F. Costa Filho. "Applying Convolutional Neural Networks to Detect Natural Gas Leaks in Wellhead Images", *IEEE Access*, 2020

Publication

---

21

Wafi Aziz, Afif Kasno, Nurkamilia Kamarudin, Zaidi Tumari, Shahrieel Aras, Herdy Rusnandi, Kamal Musa. "An accurate pattern classification for empty fruit bunch based on

<1 %

<1 %

<1 %

<1 %

<1 %

the age profile of oil palm tree using neural network", International Journal of Electrical and Computer Engineering (IJECE), 2019

Publication

---

22

Dongmei Hao, Jin Peng, Ying Wang, Juntao Liu, Xiya Zhou, Dingchang Zheng. "Evaluation of convolutional neural network for recognizing uterine contractions with electrohysterogram", Computers in Biology and Medicine, 2019

Publication

---

<1 %

23

Bego de Ancos, Sonia Sgroppo, Luc Plaza, M Pilar Cano. "Possible nutritional and health-related value promotion in orange juice preserved by high-pressure treatment", Journal of the Science of Food and Agriculture, 2002

Publication

---

<1 %

24

Santi Kumari Behera, Amiya Kumar Rath, Prabira Kumar Sethy. "Maturity Status Classification of Papaya Fruits based on Machine Learning and Transfer Learning Approach", Information Processing in Agriculture, 2020

Publication

---

<1 %

25

"Intelligent Learning for Computer Vision", Springer Science and Business Media LLC, 2021

Publication

<1 %

26

Yansheng Kan, Qing Zhang, Jiange Hao, Wei Wang et al. "Clinico-radiological characteristic-based machine learning in reducing unnecessary prostate biopsies of PI-RADS 3 lesions with dual validation", *European Radiology*, 2020

Publication

&lt;1 %

27

Olga Monago-Maraña, Rocío L. Pérez, Graciela M. Escandar, Arsenio Muñoz de la Peña, Teresa Galeano-Díaz. "Combination of Liquid Chromatography with Multivariate Curve Resolution-Alternating Least-Squares (MCR-ALS) in the Quantitation of Polycyclic Aromatic Hydrocarbons Present in Paprika Samples", *Journal of Agricultural and Food Chemistry*, 2016

Publication

&lt;1 %

28

Tanmay Sarkar, Alok Mukherjee, Kingshuk Chatterjee, Saule Ospandiyarovna Akhmetova et al. "Quality Assessment of Tindora (*Coccinia indica*) Using Poincare Plot and Cartesian Quadrant Analysis", *Food Analytical Methods*, 2022

Publication

&lt;1 %

29

Yaman Akbulut. "Automated Pneumonia Based Lung Diseases Classification with Robust Technique Based on a Customized Deep Learning Approach", *Diagnostics*, 2023

&lt;1 %

30

Ahmad Jahanbakhshi, Mohammad Momeny, Majid Mahmoudi, Yu-Dong Zhang.

"Classification of sour lemons based on apparent defects using stochastic pooling mechanism in deep convolutional neural networks", *Scientia Horticulturae*, 2020

Publication

---

<1 %

31

Fengwei Jia, Xuan Wang, Jian Guan, Qing Liao, Jiajia Zhang, Huale Li, Shuhan Qi. "Bi-Connect Net for salient object detection", *Neurocomputing*, 2020

Publication

---

<1 %

32

M. Erdmann, B. Fischer, M. Rieger. "Jet-parton assignment in events using deep learning ", *Journal of Instrumentation*, 2017

Publication

---

<1 %

33

Mitsuhiro Ozaki, Jagannath Aryal, Paul Fox-Hughes. "Dynamic Wildfire Navigation System", *ISPRS International Journal of Geo-Information*, 2019

Publication

---

<1 %

34

Qiang Dai, Xi Cheng, Yan Qiao, Youhua Zhang. "Agricultural Pest Super-Resolution and Identification with Attention Enhanced Residual and Dense Fusion Generative and Adversarial Network", *IEEE Access*, 2020

Publication

---

<1 %

35

Xun Yu, Dameng Yin, Chenwei Nie, Bo Ming et al. "Maize tassel area dynamic monitoring based on near-ground and UAV RGB images by U-Net model", Computers and Electronics in Agriculture, 2022

Publication

<1 %

---

Exclude quotes Off

Exclude matches Off

Exclude bibliography Off